

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and Principal characteristics

Trademark /Brand (if any)

Customer's Testing Facility (CTF) Stage used

Model/Type Ref.

Additional information (if necessary may also be reported on Page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

This CB Test Certificate is issued by the National Certification Body

Power Supply

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
United States of America

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
United States of America

see next page(s)



Additional Factories on Page 2

Input: 100-240V~,50-60Hz or 50/60Hz, 1.0A,



GT*96300-*****



Additional Information on Page 2

IEC 61558-1:2017, IEC 61558-2-16:2021

REP138510



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 2026-02-04

Signature:



Juan Z Saussey
Certification Department

Additional Information

IP20, ta 40°C. Output: 5-48VDC, Max.4.5A, Max.36W

The 1st '**' part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd '**' denotes the rated output wattage designation, which can be '01' to '36', with interval of 1.

The 3rd '**' denotes the standard rated output voltage designation, which can be '07.5', '10.5', '14.5', '19.5', '24', '36', '48'

The 4th '**' is optional deviation, subtracted from standard output voltage, which can be '-0.01' to '-11.9' with interval of 0.01, or blank to indicate no voltage different.

The 3rd '**' and 4th '**' together denote the output voltage, with a range of 5 - 48 volts. (For example, 07.5-2.5 means 7.5-2.5=5V output.)

The 5th '**' =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

=-R2 means hybrid desktop housing class II with C8 AC inlet

=-R3A means hybrid desktop housing class I or class II with functional earth with C6 AC inlet

The last * denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

The product has been also evaluated according to standard IEC 60335-1:2020 (Test report No.REP145961)

Factories


GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
United States of America

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, ,
Suzhou Jiang Su 215021
China



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 2026-02-04



Signature:

Juan Z Saussey
Certification Department